

5 000L AIRCRAFT REFUELLER



Non contractual picture

AVIATION FUEL	AVGAS
FLOW RATE	12 m ³ /h - 200 LPM
DIMENSIONS (LxWxH)	Approximately 6m x 2,5 m x 2,8m
ERGONOMICS	In conformity with TITAN AVIATION ergonomics charter
CONFORMITY	JIG 1 issue 13 EN 12312-5 EN 1361-C EI 1529 EI 1581 6th édition EN 1915-1
USE	Exclusively for airport use
PAINTING	White RAL 9010 Polyurethane

CHASSIS

DESIGN	Rigid
AXLES LAYOUT	4 x 2
DRIVING	LHD or RHD
ADR HAZMAT	Compliant
SPEED GOVERNOR	Up to 25 km/h

PLATFORM

PLATFORM	Not Applicable
COMPLIANCE	Not Applicable

TANK

USEFUL CAPACITY	5 000 L
MATERIAL	Aluminum
SHAPE	Biconical Single-compartment
LOADING	Bottom loading Fuelling side

DISTRIBUTION

	EZ CONTROL : New generation refuelling interface, robust, intuitive and favoring coordination & safety of operations. More information : www.titan-aviation.com Vehicle equipped with EZ CONTROL ACCESS Pack (see Options section for more packs)
UNDERWING LINE	Not Applicable
OVERWING LINE	1 overwing line - 12 m ³ /h - 200 LPM on hydraulic reel allowing a gravity-fed distribution
DECK UNDERWING LINE	Not Applicable
FILTRATION	Stainless steel water separator filter (FWS)
METER	Meter with electronic readout
2 ND REGULATION	Not Applicable
SAMPLING	Jar support after filtration
PIPES	304 L Stainless steel
ANTI-CORROSION PROTECTION	Hot zinc metallized structure Surfaces finishing according to TITAN AVIATION specs

ALL OUR RANGE VEHICLES ARE EQUIPPED WITH TITAN AVIATION 2.0 FUELLING MODULE, ALSO AVAILABLE INDEPENDENTLY

OPTIONS

SAFETY	
RR5-S01	Set of 2 extinguisher boxes (N/A with S02)
RR5-S02	Set of 2 extinguishers inclined/open scabbards (N/A S01)
RR5-S03	Set of 2+1 extinguishers
RR5-S05	Single handrail (pneumatical)
RR5-S06	Double handrail (pneumatical)
RR5-S07	Camera + Screen : mounted at the back (reverse)
RR5-S09	L&R sides protection guards
RR5-S10	Reflecting stripes
RR5-S11	Bonding reel on opposite side
RR5-S13	Access cab handles with colored safety code
RR5-S15	Wheel chock with its support

OPERATION	
RR5-O02	External suction
RR5-O03	Large display
RR5-O04	Tank mechanical gauge
RR5-O06	2"1/2 aviation coupling on bottom loading
RR5-O07	4" industrial coupling on bottom loading
RR5-O08	Customer's logo stickers
RR5-O09	Scully tank level sensor
RR5-O10	Towing pin for towable ladder (3,5t max)
RR5-O11	Ladder 3+1 with support (N/A with O12 & O13)
RR5-O12	Ladder 4+1 with support (N/A with O11 & O13)
RR5-O13	Ladder 5+1 with support (N/A with O11 & O12)

FREEZE	
RR5-F01	Cabinet with rolling doors
RR5-F02	Cabinet with swivelling doors on both sides

COMFORT	
RR5-C02	Driver seat cover
RR5-C03	Mudflaps on front of mudguards (rear is already included)
RR5-C04	Strap for driver's door opening
RR5-C05	Additional lighting system (draining points)
RR5-C08	Hose spiral protection
RR5-C09	Support inside cab for payment terminal

QUALITY	
RR5-Q01	Weight & measures dipstick (T)
RR5-Q03	Sample jar kit with CWD tray, recovery tank & reinjection
RR5-Q04	Sample jar cover protection
RR5-Q05	SSAFCON tray
RR5-Q06	Electronic thermometer and densimeter
RR5-Q07	Isolation flanges mounted on tank suction and foam return lines
RR5-Q08	Ticket printer inside cab

INNOVATION		
RR5-I02	EZ Control - Access+ pack	
RR5-I03	EZ Control - Connect pack	
RR5-I04	EZ Control - Premium pack	
RR5-I05	EZ Fuelling Start & Stop	

HOMOLOGATION	
RR5-H01	MID homologation
RR5-H02	Official tank calibration



www.titan-aviation.com